

## QUICK REFERENCE GUIDE

Illumiline SL

ILUMINARC®

### DMX Values

#### ARC1 (3 Channels)

Channel	Function	Value	Percent/Setting
1	Red	000 ⇔ 255	0–100%
2	Green	000 ⇔ 255	0–100%
3	Blue	000 ⇔ 255	0–100%

#### ARC1+D (4 Channels)

Channel	Function	Value	Percent/Setting
1	Dimmer	000 ⇔ 255	0–100%
2	Red	000 ⇔ 255	0–100%
3	Green	000 ⇔ 255	0–100%
4	Blue	000 ⇔ 255	0–100%

#### ARC2 (4 Channels)

Channel	Function	Value	Percent/Setting
1	Red	000 ⇔ 255	0–100%
2	Green	000 ⇔ 255	0–100%
3	Blue	000 ⇔ 255	0–100%
4	Lime	000 ⇔ 255	0–100%

#### ARC2+D (5 Channels)

Channel	Function	Value	Percent/Setting
1	Dimmer	000 ⇔ 255	0–100%
2	Red	000 ⇔ 255	0–100%
3	Green	000 ⇔ 255	0–100%
4	Blue	000 ⇔ 255	0–100%
5	Lime	000 ⇔ 255	0–100%

## QUICK REFERENCE GUIDE

**ILUMINARC®**

Illumiline SL

### ARC FULL (8 Channels)

Channel	Function	Value	Percent/Setting
1	Dimmer	000 ⇔ 255	0–100%
2	Red	000 ⇔ 255	0–100%
3	Green	000 ⇔ 255	0–100%
4	Blue	000 ⇔ 255	0–100%
5	Preset Color	000 ⇔ 010	No function
		011 ⇔ 020	Light Salmon
		021 ⇔ 025	Scarlet
		026 ⇔ 030	Flame Red
		031 ⇔ 045	Dark Salmon
		046 ⇔ 050	Sunset Red
		051 ⇔ 060	CID (To Tungsten)
		061 ⇔ 065	Soft Golden Amber
		066 ⇔ 070	Urban Sodium
		071 ⇔ 080	LEE Yellow
		081 ⇔ 085	Ice And A Slice
		086 ⇔ 110	Dark Yellow Green
		111 ⇔ 120	Turquoise
		121 ⇔ 140	Steel Green
		141 ⇔ 145	Steel Blue
		146 ⇔ 150	Special Steel Blue
		151 ⇔ 160	New Colour Blue
		161 ⇔ 165	Dark Steel Blue
		166 ⇔ 185	Pale Violet
		186 ⇔ 200	Pretty 'n Pink
201 ⇔ 205	Follies Pink		
206 ⇔ 220	Smokey Pink		
221 ⇔ 225	Flesh Pink		
226 ⇔ 240	Pink		
241 ⇔ 255	Cherry Rose		

## QUICK REFERENCE GUIDE

Illumiline SL

ILUMINARC®

Channel	Function	Value	Percent/Setting
<b>6</b>	<b>Color Temperature</b>	000 ⇔ 009	No function
		010	1800K
		011 ⇔ 024	1801–2199K
		025	2200K
		026 ⇔ 039	2201–2699K
		040	2700K
		041 ⇔ 054	2701–2999K
		055	3000K
		056 ⇔ 069	3001–3199K
		070	3200K
		071 ⇔ 084	3201–3999K
		085	4000K
		086 ⇔ 099	4001–4499K
		100	4500K
		101 ⇔ 114	4501–4999K
		115	5000K
		116 ⇔ 129	5001–5599K
		130	5600K
		131 ⇔ 144	5601–5999K
		145	6000K
146 ⇔ 159	6001–6499K		
160	6500K		
161 ⇔ 174	6501–6999K		
175	7000K		
176 ⇔ 189	7001–7999K		
190	8000K		
191 ⇔ 204	8001–9999K		
205 ⇔ 255	10000K		
<b>7</b>	<b>Strobe</b>	000 ⇔ 009	No function
		010 ⇔ 255	Strobe, 1–25 Hz
<b>8</b>	<b>Dimmer Speed</b>	000 ⇔ 009	No function
		010 ⇔ 029	Dimmer speed OFF
		030 ⇔ 069	Dimmer speed 1 (fastest)
		070 ⇔ 129	Dimmer speed 2
		130 ⇔ 189	Dimmer speed 3
		190 ⇔ 255	Dimmer speed 4 (slowest)

### SOLID (1 Channel)

Channel	Function	Value	Percent/Setting
<b>1</b>	<b>Dimmer</b>	000 ⇔ 255	All LEDs (0–100%)

## QUICK REFERENCE GUIDE

### SPECIAL1 (7 Channels)

Channel	Function	Value	Percent/Setting
1	Dimmer	000 ⇔ 255	0–100%
2	Strobe	000 ⇔ 009 010 ⇔ 255	No function Strobe, 1–25 Hz
3	Dimmer Speed	000 ⇔ 009 010 ⇔ 029 030 ⇔ 069 070 ⇔ 129 130 ⇔ 189 190 ⇔ 255	No function Dimmer speed OFF Dimmer speed 1 (fastest) Dimmer speed 2 Dimmer speed 3 Dimmer speed 4 (slowest)
4	Red	000 ⇔ 255	0–100%
5	Green	000 ⇔ 255	0–100%
6	Blue	000 ⇔ 255	0–100%
7	Lime	000 ⇔ 255	0–100%

### SPECIAL2 (9 Channels)

Channel	Function	Value	Percent/Setting
1	Dimmer	000 ⇔ 255	0–100%
2	Red	000 ⇔ 255	0–100%
3	Green	000 ⇔ 255	0–100%
4	Blue	000 ⇔ 255	0–100%
5	Lime	000 ⇔ 255	0–100%
6	Preset Color	000 ⇔ 010 011 ⇔ 020 021 ⇔ 025 026 ⇔ 030 031 ⇔ 045 046 ⇔ 050 051 ⇔ 060 061 ⇔ 065 066 ⇔ 070 071 ⇔ 080 081 ⇔ 085 086 ⇔ 110 111 ⇔ 120 121 ⇔ 140 141 ⇔ 145 146 ⇔ 150 151 ⇔ 160 161 ⇔ 165 166 ⇔ 185 186 ⇔ 200 201 ⇔ 205 206 ⇔ 220 221 ⇔ 225 226 ⇔ 240 241 ⇔ 255	No function Light Salmon Scarlet Flame Red Dark Salmon Sunset Red CID (To Tungsten) Soft Golden Amber Urban Sodium LEE Yellow Ice And A Slice Dark Yellow Green Turquoise Steel Green Steel Blue Special Steel Blue New Colour Blue Dark Steel Blue Pale Violet Pretty 'n Pink Follies Pink Smokey Pink Flesh Pink Pink Cherry Rose

QUICK REFERENCE GUIDE

Illumiline SL

ILUMINARC®

Channel	Function	Value	Percent/Setting
7	Color Temperature	000 ⇔ 009	No function
		010	1800K
		011 ⇔ 024	1801–2199K
		025	2200K
		026 ⇔ 039	2201–2699K
		040	2700K
		041 ⇔ 054	2701–2999K
		055	3000K
		056 ⇔ 069	3001–3199K
		070	3200K
		071 ⇔ 084	3201–3999K
		085	4000K
		086 ⇔ 099	4001–4499K
		100	4500K
		101 ⇔ 114	4501–4999K
		115	5000K
		116 ⇔ 129	5001–5599K
		130	5600K
		131 ⇔ 144	5601–5999K
		145	6000K
146 ⇔ 159	6001–6499K		
160	6500K		
161 ⇔ 174	6501–6999K		
175	7000K		
176 ⇔ 189	7001–7999K		
190	8000K		
191 ⇔ 204	8001–9999K		
205 ⇔ 255	10000K		
8	Strobe	000 ⇔ 009	No function
		010 ⇔ 255	Strobe, 1–25 Hz
9	Dimmer Speed	000 ⇔ 009	No function
		010 ⇔ 029	Dimmer speed OFF
		030 ⇔ 069	Dimmer speed 1 (fastest)
		070 ⇔ 129	Dimmer speed 2
		130 ⇔ 189	Dimmer speed 3
		190 ⇔ 255	Dimmer speed 4 (slowest)